

AP 100



AP 200



AP 300



AP 300 S



ACCUENERGIE (WH)	94	187	227	281
ACCULAADTIJD (MIN) CAPACITEIT: 80%/100%				
AL 101	75 / 100	150 / 200	190 / 250	230 / 300
AL 300	30 / 45	40 / 55	45 / 60	55 / 70
AL 500	30 / 45	30 / 45	25 / 35	30 / 45
AUTONOMIE PER ACCULADING (TOT ... MIN) [Ⓞ]				
STIHL MSA 160 C-B	-	42	50	62
STIHL MSA 200 C-B	-	42	45	56
STIHL MSA 220 C-B NIEUW	-	42	45	48
STIHL MSA 161 T	-	42	50	62
STIHL HTA 65	18	42	55	68
STIHL HTA 85	18	42	55	68
STIHL KMA 130 R (MET FS-KM, MAAIKOP MET MAAIDRADEN) [Ⓞ]	16 - 7 [Ⓞ]	30 - 14 [Ⓞ]	38 - 18 [Ⓞ]	47 - 22 [Ⓞ]
STIHL KMA 130 R (MET FS-KM, GRASSNIJBLAD) [Ⓞ]	29 - 16 [Ⓞ]	60 - 30 [Ⓞ]	75 - 40 [Ⓞ]	93 - 50 [Ⓞ]
STIHL FSA 65	30	60	75	93
STIHL FSA 85	18	36	45	56
STIHL FSA 90 R (MET MAAIKOP MET MAAIDRADEN)	12	24	30	37
STIHL FSA 90 (MET GRASSNIJBLAD)	18	36	45	56
STIHL FSA 130 R (MET MAAIKOP MET MAAIDRADEN)	19 - 10 [Ⓞ]	30 - 18 [Ⓞ]	40 - 20 [Ⓞ]	50 - 25 [Ⓞ]
STIHL FSA 130 (MET GRASSNIJBLAD)	36 - 18 [Ⓞ]	72 - 36 [Ⓞ]	85 - 45 [Ⓞ]	105 - 56 [Ⓞ]
STIHL HSA 66	72	144	180	223
STIHL HSA 86	72	144	180	223
STIHL HSA 94 R	54 - 42 [Ⓞ]	108 - 84 [Ⓞ]	135 - 105 [Ⓞ]	167 - 130 [Ⓞ]
STIHL HSA 94 T	54 - 42 [Ⓞ]	108 - 84 [Ⓞ]	135 - 105 [Ⓞ]	167 - 130 [Ⓞ]
STIHL HLA 65	72	144	180	223
STIHL HLA 85	72	144	180	223
STIHL BGA 85	10	19	24	30
STIHL BGA 86 NIEUW	11	17	21	26
STIHL BGA 100	32 - 8 [Ⓞ]	66 - 12 [Ⓞ]	83 - 16 [Ⓞ]	103 - 20 [Ⓞ]
STIHL KGA 770	84	168	210	260
STIHL TSA 230	7	14	18	22
STIHL RMA 443/RMA 443 C/ RMA 443 TC	240	420	500	620
STIHL RMA 448 PC NIEUW / RMA 448 TC	180	360	450	560
STIHL RMA 765 V NIEUW	-	-	330	400
STIHL RMA 2 RP/RMA 2 RT	240	420	500	620

■ AANBEVOLEN ACCU
 ■ VERMINDERD VERMOGEN VAN DE MACHINE

Ⓞ DE OPGEGEVEN LOOPTIJDEN PER ACCULADING EN OPPERVLAKTES ZIJN RICHTWAARDEN EN KUNNEN SCHOMMELEN VOLGENS GEBRUIK EN MAAIGOED